



EXHAUST GALLERY WITH CAPACITY FOR 05 MACRO PROOFS

TE-005/50-GE

Used in the exhaust and aspiration of gases in macro tubes in the process of acid digestion with digester block.

Technical Characteristics

TE-005/50-GE

- Capacity: 5 macro tubes Ø 50 x 250 mm divided into 1 borosilicate glass manifold;
- Header: Borosilicate glass for suction with flange;
- Sealing rings: Teflonized for threaded pipes;
- Structure: 304 stainless steel;
- Dimensions: L = 500 X D=155 x H=435 mm;
- Weight: 3kg;
- ACCOMPANY: - Glassware (except macro tube);

Benefits and Advantages

- Made of 304 stainless steel that provides high strength
- The part used to transport the tubes is made of aluminum light material for easy movement
- Presence of single manifold which allows the use of only one vacuum pump (Scrubber) for the 5 samples
- The Fixing Ring joints and outlet connection are made of teflon which is an inert material and resistant to acid gases which ensures resistance
- Presence of handles in Bakelite material that supports high temperatures ensuring longer service life to the equipment
- Strict quality control in which checks and tests ensure the perfect operation of the equipment providing safety and customer satisfaction
- Customer service to answer questions and provide explanations about the equipment and methodologies
- Possibility of adaptations according to the needs of the customer makes the line equipment a special equipment.